

Cat.6A 90° S/FTP Quick Solution - Keystone Jack



CAT 6A S/FTP Shielded Keystone Jack is designed to comply with ANSI/TIA-568-2.D for Cat.6A (ISO/IEC 11801). Compatible with SYSThames One Punch Tool which can reduce jack termination time and save time up to 8 times compared to traditional termination.

Features

Fully Shielded

Zinc-Alloy Housing

Front Connection Spring Wire: Phosphor Bronze Alloy. Plated with 50 micro-inch of Gold over 70-100 micro-inch of Nickel IDC Material: Phosphor Bronze Alloy with 10 micro-inch 100% Tin Alloy

Can terminate stranded or solid 22~24WG wires.

T568A/B wiring

Applications

Voice

10GBASE-T Ethernet

100BASE-TX Fast Ethernet

1000BASE-TX Gigabit Ethernet

1000BASE-T Gigabit Ethernet

10BASE-TX Ethernet

ATM CB1G

155/622 Mbps ATM

100 Mbps TP-PMD

100VG-AnyLAN

4/16 Mbps Token Ring

Standards

UL 1863 Safety listed UL 94V-0 flammability ANSI/TIA Standard 568-2.D ISO/IEC 11801 2. Ed. CENELEC EN 50173

Available Colours

2017-41230 - Metallic Grey



















